

Cat6 Plenum UTP Pure Copper

SKU: TS-PBC/6-BL

23AWG • 4 Twisted Pairs • CMP • U/UTP
550MHz • Solid Bare Copper



Packaging Available

1000ft Pull Box

Jacket Colors



Key Features

- Bandwidth tested up to 550 MHz • 23 AWG
- Solid Bare Copper
- Easily Identified Color Striped Pairs
- Sequential Footage Markings Every 2ft
- RoHS compliant
- Exceeds EIA/TIA 568 C.2-1, CSA, and ISO/IEC 11801 specifications
- Sequential Footage Markings Every 2ft

Print Legend

CAT6 550MHz CMP PLENUM UTP 4-PAIR
23AWG EIA/TIA-568-C.2-1
0002FT-1000FT

Technical Data

Operating Temp. Range 75°C/167°F


Max. Operating Voltage 300v

Bend Radius 2in/5mm

Insulation	HDPE
Average Thickness	0.220
Min Point Thickness	0.200
Conductor Insulation Dia. (±0.01mm)	0.95
Twisted Pair Dia. (±0.02mm)	2.02
Spline	PE

Jacket	CMP-PVC
Average Thickness	0.50 0.45
Min. Point Thickness	6.00 Yes
Overall Diameter (±0.1mm)	
Ripcord	

Conductor	Solid Bare Copper
Size	23AWG
Conductor Dia. (±0.05mm)	0.57



Color of Pairs

Pair 1	Blue- White/Blue
Pair 2	Orange- White/Orange
Pair 3	Green- White/Green
Pair 4	Brown- White/Brown





Cable ID: 225-C UTP4 CAT6 UTP CAT6 BC-TS

Test Limit: TIA Cat 6 Perm. Link

Limits Version: V7.5 Date / Time:
07/09/2021 01:14:46 PM Operator:
LIXIAOHONG Headroom 3.5 dB
(NEXT 1,2-3,6) Cable Type: Cat 6
U/UTP NVP: 69.0%

Main: Versiv

S/N: 2034142
Software Version: V6.5 Build 5
Calibration Date: 12/23/2020
Adapter: DSX-8000 (DSX-PLA804)
S/N: 20475125

Remote: Versiv

S/N: 2035009
Software Version: V6.5 Build 5
Calibration Date: 12/23/2020
Adapter: DSX-8000R (DSX-PLA804)
S/N: 20485133

Test Summary: PASS

Length (ft), Limit 295	[Pair 3,6]	305
Prop. Delay (ns), Limit 498	[Pair 7,8]	464
Delay Skew (ns), Limit 44	[Pair 7,8]	15
Resistance (ohms)	[Pair 7,8]	15.53
Insertion Loss Margin (dB)	[Pair 7,8]	1.6
Frequency (MHz)	[Pair 7,8]	250.0
Limit (dB)	[Pair 7,8]	31.1

Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	1,2-3,6	3,6-4,5	1,2-4,5
NEXT (dB)	3.9	3.5	6.0	5.5
Freq. (MHz)	35.5	80.8	246.0	210.5
Limit (dB)	49.1	43.3	35.5	36.6
Worst Pair	3,6	3,6	3,6	1,2
PS NEXT (dB)	5.2	4.4	6.2	6.0
Freq. (MHz)	5.5	83.8	236.0	220.5
Limit (dB)	59.6	40.6	33.1	33.6


PASS	MAIN	SR	MAIN	SR
Worst Pair	3,6-1,2	3,6-1,2	3,6-1,2	3,6-1,2
ACR-F (dB)	2.0	1.8	2.0	1.9
Freq. (MHz)	209.5	151.0	209.5	208.5
Limit (dB)	17.8	20.6	17.8	17.8
Worst Pair	1,2	1,2	1,2	1,2
PS ACR-F (dB)	4.3	4.3	4.3	4.3
Freq. (MHz)	209.0	208.5	209.0	208.5
Limit (dB)	14.8	14.8	14.8	14.8

N/A	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	1,2-3,6	3,6-4,5	1,2-3,6
ACR-N (dB)	4.5	4.5	7.9	10.1
Freq. (MHz)	35.5	80.8	246.0	247.0
Limit (dB)	38.4	26.8	4.6	4.5
Worst Pair	3,6	3,6	3,6	1,2
PS ACR-N (dB)	5.5	5.5	9.4	10.2
Freq. (MHz)	5.5	83.8	250.0	247.5
Limit (dB)	55.5	23.7	1.6	1.9

PASS	MAIN	SR	MAIN	SR
Worst Pair	3,6	3,6	4,5	3,6
RL (dB)	6.6	4.3	8.7	8.8
Freq. (MHz)	3.8	3.8	247.5	234.5
Limit (dB)	21.0	21.0	10.1	10.3

Compliant Network Standards:
10BASE-T 100BASE-TX
100BASE-T 2.5GBASE-T
ATM-25 ATM-61
100VG-AnyLan TR-4
TR-16 Passive

100BASE-T4
5GBASE-T
ATM-155
TR-16 Active



LinkWare™ PC Version 10.7

Electrical Characteristics

Frequency MHz	Return Loss Min (dB)	Attenuation Max (dB/100m)	Next (Min dB)
1 4 8	20.0	2.0	65.3
16	23.0	4.1	56.3
20	24.5	5.8	51.8
62.5	26.0	8.2	47.3
100	26.5	9.3	45.8
200	25.0	17.0	38.4
250	25.0	22.0	35.3
300	18.0	32.4	30.8
400	17.3	36.9	29.3
550	16.8	41.0	28.2
	15.9	48.5	26.3
	14.9	58.8	24.2

Frequency MHz	PSNEXT Min (dB)	ELFEXT Min (dB/100m)	PSELFEXT Min (dB/100m)	Delay Max (ns/100m)
1 4 8	62.3	63.8	60.8	570.0
16	53.3	51.7	48.7	552.0
20	48.8	45.7	42.7	546.7
62.5	44.3	39.7	36.7	543.0
100	42.8	37.7	34.7	542.0
200	35.4	27.8	24.8	538.6
250	32.3	23.8	20.8	537.6
300	27.8	17.7	14.7	536.5
400	26.3	15.8	12.8	536.3
550	25.2	14.2	11.2	536.1
	23.3	11.7	8.7	535.8
	21.2	8.9	5.9	535.5

1.0-100.0MHz Impedance(ohms) 100 ± 15

1.0-100.0MHz Delay Skew(ns/100m) <=45

**Pair-to-Ground Capacitance
Unbalance (pF/100m)** <=3300

**Max. Conductor DC Resistance
20oC (ohms/km)** 72.2

Resistance Unbalance (%) <=5

Mechanical Characteristics

Test Object	Jacket	PVC
Test Material	>=13.8	>=150
Before Tensile Strength (Mpa)	100x168	
Aging Elongation (%)	>=85%	of
Aging Condition (°Cxhrs)	unaged	
After Tensile Strength (Mpa)	>=50%	of
Aging Elongation (%)	unaged	No
Cold Bend (-20+2° Cx4hrs)	Crack	

Returns? No problem.
Guarantee? Of course

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.