

Cat6A Unshielded Plenum

SKU TS-PBC/6A-RD

750MHz • Solid Copper



Key Features

- Bandwidth tested up to 750 MHz
- Suitable for 1 and 10-Gigabit Ethernet
- Easily Identified Color Striped Pairs
- Sequential Footage Markings Every 2ft
- In compliance with ANSI/TIA 568.2-D
- RoHS-3 compliant
- Supports PoE, PoE+, and PoE++ (IEEE 802.3af/at/bt) up to 60W & 300V DC

Print Legend

CAT6A 750MHz CMP PLENUM UTP 4-PAIR 23AWG EIA/TIA-568-C.2-1 0002FT-1000FT

Technical Data

Operating Temp. Range 75°C/167°F

Max. Operating Voltage 300v

Bend Radius 2in/5mm

Insulation		HDPE
Average Thickness		0.250
Min Point Thickness		0.230
Conductor Insulation Dia. (±0.01mm)		1.08
Twisted Pair Dia. (±0.02mm)		2.16
Spline		PE
Jacket		CMP-PVC
Average Thickness		0.55
Min. Point Thickness		0.50
Overall Diameter (±0.1mm)		6.20
Ripcord		Yes
Conductor		Solid Bare Copper
Size		23AWG
Conductor Dia. (±0.05mm)		0.58



Color of Pairs

Pair 1	Blue- White/Blue
Pair 2	Orange- White/Orange
Pair 3	Green- White/Green
Pair 4	Brown- White/Brown

Electrical Characteristics

Frequency MHz	Return Loss Min (dB)	Attenuation Max (dB/100m)	Next (Min dB)
1	20.0	2.1	74.3
4	23.0	3.8	65.3
8	24.5	5.3	60.8
16	25.0	7.5	56.2
20	25.0	8.4	54.8
62.5	21.5	15.0	47.4
100	20.1	19.1	44.3
200	18.0	27.6	39.8
250	17.3	31.1	38.3
300	16.8	34.3	37.1
500	15.2	45.3	33.8
750	14.0	62.3	31.1

Frequency MHz	PSNEXT Min (dB)	ELFEXT Min (dB/100m)	PSELFEXT Min (dB/100m)	Delay Max (ns/100m)
1	72.3	67.8	64.8	570.0
4	63.3	55.8	52.8	552.0
8	58.8	49.7	46.7	546.7
16	54.2	43.7	40.7	543.0
20	52.8	41.8	38.8	542.0
62.5	45.4	31.9	28.9	538.6
100	42.3	27.8	24.8	537.6
200	37.8	21.8	18.8	536.5
250	36.3	19.8	16.8	536.3
300	35.1	18.3	15.3	536.1
500	31.8	13.8	10.8	535.6
750	29.1	10.3	7.3	535.3

1.0-100.0MHz Impedance (ohms) 100 ± 15

1.0-100.0MHz Delay Skew (ns/100m) ≤45

Pair-to-Ground Capacitance Unbalance (pF/100m) ≤3300

Max. Conductor DC Resistance 20oC (ohms/km) 72.2

Resistance Unbalance (%) ≤5

Mechanical Characteristics

Test Object	Jacket
Test Material	PVC
Before Tensile Strength (Mpa)	≥13.8
Aging Elongation (%)	≥150
Aging Condition (°Cxhrs)	100x168
After Tensile Strength (Mpa)	≥85% of unaged
Aging Elongation (%)	≥50% of unaged
Cold Bend (-20+2° Cx4hrs)	No Crack

We Ship direct from our high service warehouse.

Returns? No problem.
Guarantee? Of course

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.